





CAT. 6 FTP 4x2x23AWG



CONSTRUCTION

Inner conductor	Solid Bare Copper	$\Phi 0.57 \pm 0.02\text{mm}$
Insulation	Solid HDPE	$\Phi 1.16 \pm 0.05\text{mm}$
	Color	1 Blue & White/ Blue 2 Orange & White/ Orange 3 Green & White/ Green 4 Brown & White/ Brown
	Filler	PE “+” shape
Shield	Total Shield	Foil
	Drain wire	Tinned Copper 26AWG
Sheath	PVC, PE, FRPVC, LSZH	$\Phi 7.20 \pm 0.30\text{mm}$
	Rip cord	Nylon (Optional)

MECHANICAL PROPERTIES

Bending radius (single)	mm	$8 \times \text{cable OD}$
-------------------------	----	----------------------------

ELECTRICAL PROPERTIES

Impedance	Ω	$100 \pm 15 @ \leq 100\text{MHz}$
		$100 \pm 25 @ 100 \sim 250 \text{ MHz}$
DC Resistance unbalance	For conductors, %	≤ 2
	For pairs, %	≤ 4
Conductor DC Resistance	$\Omega/100\text{m}$	$\leq 9.5 @ 20^\circ\text{C}$
Insulation Resistance	$\text{M}\Omega.\text{km}$	≥ 5000
Delay Skew	ns/100	≤ 45



CAT. 6 UTP 4x2x23AWG

Frequency	Attenuation	Return loss	NEXT	PS NEXT	EL FEXT	PS EL FEXT	Delay
MHz	dB/100m	dB	dB	dB	dB	dB	ns/100m
4	3.8	23.0	66.3	63.3	56.0	53.0	552
8	5.3	24.5	61.8	58.8	49.9	46.9	547
10	6.0	25.0	60.3	57.3	48.0	45.0	545
16	7.6	25.0	57.2	54.2	43.9	40.9	543
20	8.5	25.0	55.8	52.8	42.0	39.0	542
25	9.5	24.3	54.3	51.3	40.0	37.0	541
31.25	10.7	23.6	52.9	49.9	38.1	35.1	540
62.5	15.4	21.5	48.4	45.4	32.1	29.1	539
100	19.8	20.1	45.3	42.3	28.0	25.0	538
200	29.0	18.0	40.8	37.8	22.0	19.0	537
250	32.8	17.3	39.3	36.3	20.0	17.0	536

STANDARDS
